



63206LLU Bearing 2D drawings and 3D CAD models

30,000 mm x 62,000 mm x 23,800 mm NTN  
63206LLU deep groove ball bearings

Bearing No. 63206LLU

Size	30x62x23.800 mm
Bore Diameter	30,000 mm
Outer Diameter	62,000 mm
Width	23,800 mm
d	30,000 mm
D	62,000 mm
B	23,800 mm
C	23,800 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359581140
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric



## Shandong Jiangshan Industrial Develop...

Long Description	30MM Bore; 62MM Outside Diameter; 23.825MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Ca
Other Features	Deep Groove   Cartridge Type   Double Lip Friction Nitrile Rubber Seal   -20 To 120 Deg C   Shell Alvania Prelubricated
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Weight / LBS	0.63
Inner Race Width	0 Inch   0 Millimeter
Outside Diameter	2.441 Inch   62 Millimeter
Outer Race Width	0.938 Inch   23.825 Millimeter
Bore	1.181 Inch   30 Millimeter
bore diameter:	30 mm
precision rating:	ISO Class 0
outside diameter:	62 mm
finish/coating:	Uncoated
overall width:	23.8 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed



## Shandong Jiangshan Industrial Develop...

inner ring width:	23.80 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	23.80 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	7300 rpm
internal clearance:	CN
fillet radius:	1 mm
operating temperature range:	-40 to 120 ° C
series:	632
dynamic load capacity:	5100 N
manufacturer product page:	<a href="#">Click here</a>
static load capacity:	2390 N